



BARCOAT ISOLATOR

Safety Data Sheet BAR-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/17/2015

Revision date: 05/24/2019

Supersedes: 11/24/2017

Version: 3.0

DRIVING SURFACE PERFECTION

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : BARCOAT ISOLATOR
 Product code : BAR/1
 UP Number : UP0720

1.2. Recommended use and restrictions on use

Recommended use : Primer

1.3. Supplier

U-POL US Inc
 108 Commerce Way
 Easton PA 18040 - USA
 T 1-800-340-7824 - F 1-800-787-5150
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

| | |
|---|-----------------------------------|
| Flammable liquids Category 2 | Highly flammable liquid and vapor |
| Serious eye damage/eye irritation Category 2 | Causes serious eye irritation |
| Carcinogenicity Category 1A | May cause cancer |
| Specific target organ toxicity (single exposure) Category 1 | Causes damage to organs |

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : Highly flammable liquid and vapor
 Causes serious eye irritation
 May cause cancer
 Causes damage to organs

Precautionary statements (GHS US) : Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not breathe vapors, fume, spray.
 Wash hands thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Wear face protection, protective clothing, protective gloves.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If exposed or concerned: Get medical advice/attention.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|------------------------|----------------------|--------|--|
| ethanol, ethyl alcohol | (CAS-No.) 64-17-5 | 5 - 43 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 1A, H350 |
| talc | (CAS-No.) 14807-96-6 | 5 - 23 | Carc. 2, H351 |
| propan-2-ol | (CAS-No.) 67-63-0 | 5 - 23 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| titanium(IV) oxide | (CAS-No.) 13463-67-7 | 5 - 23 | Carc. 2, H351 |
| methanol | (CAS-No.) 67-56-1 | < 5 | Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370 |
| carbon black | (CAS-No.) 1333-86-4 | < 5 | Carc. 2, H351 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor.
Reactivity : Highly flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, fume, spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, fume, spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Storage temperature : < 25 °C
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| titanium(IV) oxide (13463-67-7) | | |
|----------------------------------|-------------------------------------|--|
| ACGIH | Local name | Titanium dioxide |
| ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| ACGIH | Remark (ACGIH) | TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) |
| ACGIH | Regulatory reference | ACGIH 2019 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| carbon black (1333-86-4) | | |
| ACGIH | Local name | Carbon black |
| ACGIH | ACGIH TWA (mg/m ³) | 3 mg/m ³ (Inhalable fraction) |
| ACGIH | Remark (ACGIH) | TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans) |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 3.5 mg/m ³ |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| ethanol, ethyl alcohol (64-17-5) | | |
| ACGIH | Local name | Ethanol |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm |
| ACGIH | Remark (ACGIH) | URT irr |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1900 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| methanol (67-56-1) | | |
|------------------------------|-------------------------------------|---|
| ACGIH | Local name | Methanol |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| ACGIH | Remark (ACGIH) | Headache; eye dam; dizziness; nausea |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| propan-2-ol (67-63-0) | | |
| ACGIH | Local name | 2-Propanol |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 400 ppm |
| ACGIH | Remark (ACGIH) | Eye & URT irr; CNS impair |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 980 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 400 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| talc (14807-96-6) | | |
| ACGIH | Local name | Talc |
| ACGIH | ACGIH TWA (mg/m ³) | 2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica) 0.1 fibers/cm ³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination) |
| ACGIH | ACGIH TWA (ppm) | 0.1 fibers/cm ³ (Containing asbestos fibers. F - Respirable fibers) |
| ACGIH | Remark (ACGIH) | Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen) |
| ACGIH | Regulatory reference | ACGIH 2019 |
| OSHA | OSHA PEL (TWA) (ppm) | 20 mppcf |
| OSHA | Remark (OSHA) | Table Z-3. CAS No. source: eCFR Table Z-1. |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-3 Mineral Dusts |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Appearance | : Liquid. : Slightly yellow to green : alcoholic |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : > 35 °C |
| Flash point | : 19 °C |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : No data available |
| Specific gravity / density | : ≈ 1.15 (1.14 - 1.16) g/cm ³ |
| Solubility | : Miscible with water. soluble in most organic solvents. |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : ≈ |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

| | |
|----------------------------|-------------------------|
| As Packaged Regulatory VOC | : 529 g/l (4.41 lb/gal) |
| As Packaged Actual VOC | : 469 g/l (3.91 lb/gal) |
| Percent Solids | : 47.99 wt% |

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

| titanium(IV) oxide (13463-67-7) | |
|---|---|
| LD50 oral rat | > 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s)) |
| LC50 inhalation rat (mg/l) | > 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s)) |
| carbon black (1333-86-4) | |
| LD50 oral rat | > 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral) |
| LD50 dermal rabbit | > 3000 mg/kg (Rabbit, Literature study, Dermal) |
| LC50 inhalation rat (mg/l) | > 4.6 mg/l air (4 h, Rat, Experimental value, Inhalation) |
| ethanol, ethyl alcohol (64-17-5) | |
| LD50 oral rat | 10740 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral) |
| LD50 dermal rabbit | > 16000 mg/kg (Rabbit, Literature study, Dermal) |
| LC50 inhalation rat (mg/l) | 117 - 125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value, Inhalation) |
| ATE US (oral) | 10740 mg/kg body weight |
| methanol (67-56-1) | |
| LD50 oral rat | 1187 - 2769 mg/kg body weight (BASF test, Rat, Male/female, Weight of evidence, Aqueous solution, Oral, 7 day(s)) |
| LD50 dermal rabbit | 17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal) |
| LC50 inhalation rat (mg/l) | 128.2 mg/l air (BASF test, 4 h, Rat, Male/female, Experimental value, Inhalation (vapours)) |
| ATE US (oral) | 100 mg/kg body weight |
| ATE US (dermal) | 300 mg/kg body weight |
| ATE US (gases) | 700 ppmV/4h |
| ATE US (vapors) | 3 mg/l/4h |
| ATE US (dust, mist) | 0.5 mg/l/4h |
| propan-2-ol (67-63-0) | |
| LD50 oral rat | 5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | 16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s)) |
| LC50 inhalation rat (ppm) | > 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male/female, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 5840 mg/kg body weight |
| ATE US (dermal) | 16400000 mg/kg body weight |
| talc (14807-96-6) | |
| LD50 oral rat | > 5000 mg/kg body weight |
| LD50 dermal rat | > 2000 mg/kg body weight |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

| | |
|---|--|
| titanium(IV) oxide (13463-67-7) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| carbon black (1333-86-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| ethanol, ethyl alcohol (64-17-5) | |
| IARC group | 1 - Carcinogenic to humans |
| propan-2-ol (67-63-0) | |
| IARC group | 3 - Not classifiable |
| talc (14807-96-6) | |
| IARC group | 3 - Not classifiable, 2B - Possibly carcinogenic to humans |

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Causes damage to organs.

| | |
|--|--------------------------|
| methanol (67-56-1) | |
| Specific target organ toxicity – single exposure | Causes damage to organs. |

| | |
|--|------------------------------------|
| propan-2-ol (67-63-0) | |
| Specific target organ toxicity – single exposure | May cause drowsiness or dizziness. |

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

| | |
|---|--|
| titanium(IV) oxide (13463-67-7) | |
| LC50 fish 1 | 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration) |
| ErC50 (algae) | 61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) |
| carbon black (1333-86-4) | |
| LC50 fish 1 | > 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Literature study) |
| EC50 Daphnia 1 | > 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| ethanol, ethyl alcohol (64-17-5) | |
| LC50 fish 1 | 14200 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value) |
| methanol (67-56-1) | |
| LC50 fish 1 | 15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal) |
| EC50 Daphnia 1 | 18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect) |
| ErC50 (algae) | 22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value) |
| propan-2-ol (67-63-0) | |
| LC50 fish 1 | 9640 - 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal) |

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------|---|
| talco (14807-96-6) | |
| LC50 fish 1 | > 100 g/l (24 h, Brachydanio rerio, Semi-static system) |

12.2. Persistence and degradability

| | |
|--|-----------------------------------|
| titanium(IV) oxide (13463-67-7) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable (inorganic) |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |

| | |
|---------------------------------|---|
| carbon black (1333-86-4) | |
| Persistence and degradability | Biodegradability in soil: not applicable. Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |

| | |
|---|--|
| ethanol, ethyl alcohol (64-17-5) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.8 - 0.967 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.7 g O ₂ /g substance |
| ThOD | 2.1 g O ₂ /g substance |
| BOD (% of ThOD) | 0.43 |

| | |
|---------------------------------|--|
| methanol (67-56-1) | |
| Persistence and degradability | Readily biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.42 g O ₂ /g substance |
| ThOD | 1.5 g O ₂ /g substance |

| | |
|---------------------------------|--|
| propan-2-ol (67-63-0) | |
| Persistence and degradability | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.19 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.23 g O ₂ /g substance |
| ThOD | 2.4 g O ₂ /g substance |

| | |
|---------------------------------|-----------------------------------|
| talco (14807-96-6) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |

12.3. Bioaccumulative potential

| | |
|--|----------------------|
| titanium(IV) oxide (13463-67-7) | |
| Bioaccumulative potential | Not bioaccumulative. |

| | |
|---------------------------------|----------------------|
| carbon black (1333-86-4) | |
| Bioaccumulative potential | Not bioaccumulative. |

| | |
|---|---|
| ethanol, ethyl alcohol (64-17-5) | |
| BCF fish 1 | 1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across) |
| Log Pow | -0.31 (Experimental value) |

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| ethanol, ethyl alcohol (64-17-5) | |
|---|---|
| Bioaccumulative potential | Not bioaccumulative. |
| methanol (67-56-1) | |
| BCF fish 1 | 1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value) |
| Log Pow | -0.77 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| propan-2-ol (67-63-0) | |
| Log Pow | 0.05 (Weight of evidence approach, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| talc (14807-96-6) | |
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

| titanium(IV) oxide (13463-67-7) | |
|---|---|
| Ecology - soil | Low potential for mobility in soil. |
| carbon black (1333-86-4) | |
| Ecology - soil | Adsorbs into the soil. Not toxic to plants. Not toxic to animals. |
| ethanol, ethyl alcohol (64-17-5) | |
| Surface tension | 0.022 N/m (20 °C) |
| Ecology - soil | Highly mobile in soil. |
| methanol (67-56-1) | |
| Surface tension | 0.023 N/m (20 °C) |
| Log Koc | 0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |
| propan-2-ol (67-63-0) | |
| Surface tension | 0.021 N/m (25 °C) |
| Log Koc | 0.185 - 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. |

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|------------------------------|---|
| Regional legislation (waste) | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information | : Flammable vapors may accumulate in the container. |

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| | | |
|-------------|-----------------|---------|
| methanol | CAS-No. 67-56-1 | < 5% |
| propan-2-ol | CAS-No. 67-63-0 | 5 - 23% |

titanium(IV) oxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

ethanol, ethyl alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ 5000 lb

propan-2-ol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

talc (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

ethanol, ethyl alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

WARNING:

This product can expose you to carbon black, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BARCOAT ISOLATOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


| Component | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|-------------------------|-----------------|------------------------|----------------------------|------------------------------|----------------------------------|-------------------------------------|
| carbon black(1333-86-4) | X | | | | | |
| methanol(67-56-1) | | X | | | | |

| Component | State or local regulations |
|---------------------------------|--|
| titanium(IV) oxide(13463-67-7) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| carbon black(1333-86-4) | U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| talc(14807-96-6) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List |
| ethanol, ethyl alcohol(64-17-5) | U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Washington - Permissible Exposure Limits - TWAs |
| methanol(67-56-1) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Maine - Air Pollutants - Hazardous Air Pollutants; U.S. - Massachusetts - Right to Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Washington - Permissible Exposure Limits - TWAs |
| propan-2-ol(67-63-0) | U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances |

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Revision date : 05/24/2019
- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US GHS (GHS HazCom2012) - U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.