



EASY 3

DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

EXTRA SMOOTH FINISHING FILLER

DESCRIPTION

An easy to use ultra smooth finishing paste for skimming and fine finishing in thin layers prior to the paint process

- High adhesion to multiple substrates
- Ease of application
- Easy to sand

Typical Use Ideal for correcting minor imperfections such as pinholes, scratches and stonechips

Technical Data



| | |
|-------------------------|--------------|
| Appearance | Gold |
| Mixing Ratio | 2% by weight |
| Specific Gravity | 1.81 |

STORAGE & VOC INFORMATION

Shelf Life



2 years from date of manufacture (which is printed on the label) in sealed container.

Recommended Storage Temperature +5°C - +25°C

VOC Information



The EU limit for this product (category: IIbB) in ready to use form is 250g/litre. The VOC content of this product as received is 271g/litre. The VOC content of this product in ready to use form is <100 g/litre.

| Order Code | Format | Colour |
|------------|----------|--------|
| Easy3/1 | 1.1L Tin | Gold |
| | | |

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.



EASY 3

DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

EXTRA SMOOTH FINISHING FILLER

APPLICATION GUIDE

Tools Required



- Onion Board™
- U-POL Applicator
- SYSTEM 20™ Degreaser
- MAXIMUM Abrasives
- GUIDE/AL Guide Coat
- MAXIMUM Premium Masks
- MAXIMUM Painters Overalls



Surface Preparation



| | | | | | | |
|--|--------------|--------------|--------------|----------------|-------------|-------|
| | Bare Steel | Aluminium | Galvanised | Original Paint | Body Filler | GRP |
| | S2001, S2002 | S2001, S2002 | S2001, S2002 | S2001, S2002 | | S2000 |
| | P80 | P180 | P180 | P180 | P80-P180 | P180 |

- EASY3 is multifunctional and has superb adhesion to all the substrates above
- For the best results, good preparation is essential.
- Clean and degrease removing dirt, oil, grease and wax with a cleaning solution such as SYSTEM 20 degreasers.

Application



| | Mixing Ratio | Gel Time | Time to Sand |
|------|--------------|----------|--------------|
| 10°C | 3% | 6-7' | 20' |
| 20°C | 2% | 4-5' | 15-20' |
| 30°C | 1% | 4' | 15' |

| IR. | |
|------------|-------|
| Time | 5mins |
| Distance | 80cm |
| Max. Temp. | 80°C |

- Do not over or under catalyz than specified.
- Mix thoroughly on a mixing board (Onion Board).
- Apply with a pressing action reducing air entrapment.
- Not recommend for applications below 5°C

Sanding



| | |
|---------|-----------|
| Initial | P180 |
| Final | P180-P240 |

U-POL recommends a Guide Coat (GUIDE/AL) during the sanding process to identify the high and low spots

- A U-POL Finishing Filler such as DOLPHIN GLAZE can be used to fill imperfections such as pin holes and scratches prior to painting.

Over Painting



U-POL recommends a SYSTEM 20 Primer to achieve the perfect surface for the colour of your choice.



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

EASY 3

EXTRA SMOOTH FINISHING FILLER

U-POL Ltd

4th Floor, The Grange, 100 High Street
London, N14 6BN
WWW.U-POL.COM

UK Sales

T: +44 (0)20 8492 5920
F: +44 (0)20 8181 6911
uk.sales@u-pol.com

International

T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical

T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com